



- WTC-1602-PR-OF-16Size: 96(w)x96(h)x85(d) mm

- Microcontroller based, 16x2 LCD
- Supply 100- 260 V Ac
- Input J,K or PT100
- Sixteen program, Sixteen step
- Each step contain Temperature, Soaking time & Ramp setting
- Over night delay timer(Optional)
- Power down memory for delay time, Step number & soaking time
- Output: 1. Relay Contact or SSR, 2. Alarm contact or Buzzer
- On/Off Control selection
- Heating Application
- Range: J type 0-750c,
- K type 0-1200c,
- RTD type -50 to 400
- RTD.1 type -50.0 to 400.0
- Temperature As per range adjustable in set mode.
- Soak band to enable soaking timer in band
- Hysteresis 2 to 250c adjustable
- Alarm Mute facility by decrement key.
- OPEn display if Sensor break & -rEV display if connections reverse.
- End displays if process complete.
- Relay trip if sensor breaks, connection open or connection reverse.
- Calibration Error correction by front key switch (No preset setting)

WAVE INSTRUMENTS LLP

L-45/9, Phase-3, Opp. Mazda Ltd., GIDC Naroda, Ahmedabad -382330, Gujarat – INDIA

☎ +91- 9722003425, ☎ +91-79-40043425, 📞 +91-7043003425.

mail: waveinstruments@gmail.com, Website: <http://www.wavetronics.co.in>