



▪ WTC-1602-GAS...Size: 96(w)x96(h)x85(d) mm

- Microcontroller based, 16X2 LCD
- Supply 220 V Ac
- Input RTD Pt100 type
- Output: Internal wiring 1.Set Relay, 2. Alarm Output
- Heating control
- Temperature As per range adjustable in set mode
- Hysteresis 0.2 to 25.0c adjustable as per range selection
- 3 On time & 3 Off time settable for Auto On-Off as per RTC
- Burner reset time adjustable 0 to 250 minute(Reset for 5 second)
- Manual reset for burner by Increment key
- Over Heat Temperature adjustable
- Auto/Manual Operation selection
- Auto Mode: Burner On/Off as per Time & Temperature
- Manual Mode: Burner On/Off as per Temperature
- OPEn display if Sensor break
- Relay trip & give Alarm if sensor breaks or connection open
- Decrement key to mute alarm
- Temperature Indication Error correction by Software
- LED Indication for Burner, Over Heat, Alarm & Manual mode

WAVE INSTRUMENTS LLP

L-45/9, Phase-3, Opp. Mazda Ltd., GIDC Naroda, Ahmedabad -382330, Gujarat – INDIA

☎ +91- 9722003425, ☎ +91-79-40043425, 📞 +91-7043003425.

mail: waveinstruments@gmail.com, Website: <http://www.wavetronics.co.in>